



# LUBRICATION EQUIPMENT

Product Overview and Selection Guide  
for the Lubrication Professional



LUBRICATION

PROVEN QUALITY. LEADING TECHNOLOGY.



## More Than 75 Years in the Lubrication Business

Since 1926, Graco® has been a leading manufacturer of equipment for the lubrication professional. Our oil and grease pumps; dispense valves and meters; hose reels; used-oil equipment and fluid management systems are the industry standard and the first choice for the most demanding applications.

Our Lubrication Equipment Division is at the heart of a corporation now with annual revenue in excess of \$500 million.

### *What makes our lubrication equipment so special?*

- Reliable performance day after day in the most demanding environments
- Our ability to meet job requirements with high-quality equipment
- Industry leading customer support and product availability

### **LARGE DISTRIBUTION NETWORK**

As partners in the lubrication business for over 75 years, our knowledgeable worldwide distribution network provides easy access to professionals who understand the unique needs of your business and who are able to recommend the equipment that best fits your application.

### **STATE-OF-THE-ART FACILITIES**

Graco's 590,000 sq ft of manufacturing, filled with state-of-the-art equipment and over 240,000 sq ft Distribution Center, provide quality products second-to-none and ensure you'll get the equipment you need when you need it.

### **RESEARCH & DEVELOPMENT**

Graco is dedicated to 'finding the future' in products and services. Graco invests \$15 – \$20 million in product research and development each year – giving you product with a competitive edge.

### **ISO-9001 CERTIFICATION**

Graco's excellence in manufacturing is enhanced by ISO-9001 Certification.

### **CUSTOMER SERVICE**

Leading the industry with total customer support, the Graco Lubrication Equipment Division offers you a dedicated Customer Support Team throughout the world.



# Meters and Valves



## Accuracy and Control

### Meters

Graco manufactures a wide range of durable meters ideal for fleet maintenance, automotive service centers and other applications where rigorous daily routines demand rugged, accurate dispensing of motor oils, hydraulic fluids, ATF, specialty lubricants and anti-freeze. For metering grease, Graco offers the Accu-Shot™ metered grease valve with a flow rate up to 35.3 oz/min (1000 g/min).

### Valves

Graco valves are among the most important tools in the shop. The V5™ and V12™ non-metered valves are designed for dispensing oils, ATF, specialty lubricants, and anti-freeze. The Pro-Shot™, Power-Shot™, EZ-Shot™ battery powered grease gun and dispense valves offer rugged, dependable dispensing of grease.

## METERS

### OIL METERS



### GREASE METER



## VALVES

### GREASE VALVES



### OIL VALVES



# Hose Reels



## The Critical Connection

The right reel is essential for maximizing pump and meter efficiency. That's why we put the same level of craftsmanship into our hose reels as we do in our other lubrication equipment.

We offer a wide range of hose reels capable of handling lubricant oils, grease, air/water, wind-shield wash or anti-freeze.

**250 SERIES HOSE REEL:** Holds up to 25 ft (7.62 m) of 1/2 in (1.27 cm) hose and can be used in open or enclosed configurations. Heavy-duty springs, bearings and latch bolster reel life. Factory-installed hose stays flexible, even under pressure.

**350 SERIES HOSE REEL:** Handles up to 50 ft (15.24 m) of 1/2 in (1.27 cm) hose to extend coverage area. Includes multi-position hose guide for overhead mounting applications.

**500 SERIES HOSE REEL:** Dual-arm design handles up to 50 ft (15.24 m) of 1/2 in (1.27 cm) hose and includes permanently lubricated bearings for positive recoil and long life. Multi-position roller guide offers superior service in any mounting position.

**700 SERIES HOSE REEL:** Dual-arm design handles up to 75 ft (22.86 m) of 3/4 in (1.91 cm) hose. Equipped with heavy-duty ball bearings for longer life than sleeved-type bearings.

**750 SERIES HOSE REEL:** Heavy-duty, high volume reel handles up to 50 ft (15.2 m) of 1.25 in (3.17 cm) hose that is ideal for fuel dispense. Maintains desired length of hose and assures positive latch and rewind.



250 Series



350 Series



500 Series



700 Series



750 Series



# Pumps

## The 'Heart' of Your System

For pumping oils and greases, it's tough to beat these Graco pumps. Simply put, when you use a Graco pump, you're looking forward to years of reliable service from the leader in lubrication equipment.

The Fire-Ball pump has been the 'crown jewel' of Graco since the 1950s, and is the pump of choice in the most demanding environments.

**FAST-BALL®:** Ideal for transfer of oils or ATF, the 1:1 Fast-Ball's in-line design features fewer parts for minimal pump wear.

**MINI FIRE-BALL® 225:** Ideal for low to medium volume applications, the Mini Fire-Ball 225 is the latest edition to Graco's classic Fire-Ball design in a new 3:1 package!

**FIRE-BALL® 300:** Perfect for medium volume applications, the Fire-Ball 300 set the industry standard for years of reliable service. Available in ratios of 5:1, 15:1 and 50:1.

**FIRE-BALL® 425:** With a robust design, the Fire-Ball is the pump of choice for your most demanding high volume applications. Available in ratios of 3:1, 6:1, 10:1, 50:1 and 75:1.

**DIAPHRAGM PUMPS:** Ideal for a variety of applications from oil transfer and used oil to windshield wash and anti-freeze. Graco offers diaphragm pumps ranging in size from 3/8 in (9.5 mm) to 3 in (76.2 mm).



*Fast-Ball*



*Mini Fire-Ball 225*



*Fire-Ball 300*



*Fire-Ball 425*



*Diaphragm Pump*

# Fluid Management

## Matrix: Wireless Total Fluid Management System

Larger operations require a comprehensive fluid management system to minimize material waste and labor time, and accelerate service cycles.

The Matrix™ Total Fluid Management System™ provides the ultimate wireless metering, tracking and delivery system for dispensing and inventorying engine oil, gear lube, anti-freeze and transmission fluids. It provides simple tracking of all fluids dispensed, records transactions and inventory levels, and offers multi-level security.

The patented Matrix system features simple-to-install system software, state-of-the-art electronic meters and Tank Level Monitors that track of the amount of bulk fluids in storage tanks.

The meters and monitors wirelessly transmit their information to a transceiver connected to a PC – making it easier than ever to control your fluid inventory!



*Matrix Meter*



*Transceiver*



*Tank Level Monitor*

## A Full Line of Fluid Receivers to Meet Your Needs!

Collect large quantities of used oil with less mess and labor costs! With the Coolant King™, Oil King™, Oil Ace™ and Used Oil Drain, you'll be able evacuate, drain, and transfer used oil, anti-freeze and other used fluids, reliably, quickly, and in the most cost effective manner.



*Coolant King – 248632*



*Oil King – 238866*



*Oil Ace – 115599*



*Oil Drain – 239301*

# Technical Specifications and Ordering Information

## Meters and Valves

### EM5™ Electronic Meter Specifications

Flow range	0.26 to 5 gpm (1 to 18.9 lpm)
Operating pressure range for motor oil units	45 to 1000 psi (3.1 to 70 bar, 0.31 to 7 MPa)
Weight	2.5 lb (1.14 kg)
Units of measurement	pints, quarts, gallons or liters
Inlet	1/2 npt
Outlet	3/8 npt
Operating temperature range	32 to 120°F (0 to 48.8°C)
Battery	9-volt alkaline
Wetted parts	zinc, 304 SST, Zenite®, CS, polyurethane, nitrile rubber
Fluid compatibility	lubricating oils, anti-freeze mixtures
Accuracy	±0.5%

### EM5 Electronic Meter with Rigid Extension

238461	U.S. measure and Metric measure
238457	Canadian Weights & Measures Approved (available in Canada only)

### EM5 Electronic Meter with Flexible Extension

238462	U.S. measure and Metric measure
238458	Canadian Weights & Measures Approved (available in Canada only)

### EM5 Electronic Meter with Gear Lube Extension (15° Bend with 90° Elbow)

238463	U.S. measure and Metric measure
238459	Canadian Weights & Measures Approved (available in Canada only)

### PM5™ Electronic Pre-Set Meter Specifications

Flow range	0.26 to 5 gpm (1 to 18.9 lpm)
Operating pressure range	45 to 1000 psi (2.9 to 70 bar; 0.29 to 7 MPa)
Weight	3.0 lb (1.36 kg)
Units of measurement	pints, quarts, gallons or liters
Inlet	1/2 npt
Outlet	3/8 npt
Operating temperature range	32 to 120°F (0 to 48.8°C)
Battery	9-volt alkaline
Wetted parts	zinc, 304 SST, Zenite, CS, polyurethane, nitrile rubber
Fluid compatibility	lubricating oils, anti-freeze mixtures
Accuracy	±0.5%

### PM5 Electronic Pre-Set Meter, Rigid Extension

238511	U.S. measure and Metric measure
--------	---------------------------------

### PM5 Electronic Pre-Set Meter, Flexible Extension

238512	U.S. measure and Metric measure
--------	---------------------------------

### PM5 Electronic Pre-Set Meter, Off-set Extension (15° Bend with 90° Elbow)

238515	U.S. measure and Metric measure
--------	---------------------------------

### EM6™ Electronic Meter Specifications

Maximum recommended flow rate	.6 gpm (23 lpm)
Maximum operating pressure	1500 psi (103 bar; 10.3 MPa)
Operating temperature range	-40° to 180°F (-40° to 82°C)
Inlet	1/2 npt
Outlet	1/2 npt
Wetted parts	aluminum, SST, CS, acetal, nitrile rubber, Geolast™
Fluid compatibility	lubricating oils

243599	U.S. measure (rigid extension)
243600	U.S. measure (gear lube extension)
243601	U.S. measure (flexible extension)
243602	Metric measure (rigid extension)
243603	Metric measure (gear lube extension)
243604	Metric measure (flexible extension)
243992	1/2 in (12.7 mm) bare valve (without locking trigger)

# Technical Specifications and Ordering Information

## Meters and Valves (continued)

### EM12™ Electronic Meter Specifications

Maximum recommended flow rate	12 gpm (45.4 lpm)
Maximum operating pressure	1500 psi (103 bar; 10.3 MPa)
Operating temperature range	-40° to 180°F (-40° to 82°C)
Inlet	1/2 npt and 3/4 npt
Outlet	1/2 npt
Wetted parts	aluminum, SST, CS, acetal, nitrile rubber, Geolast™

### EM12™ Electronic Meter Ordering Information

3/4 npt(f) swivel inlet with:	
238636	U.S. measure 1/2 in (12.7 mm) rigid extension
238637	U.S. measure 1/2 in (12.7 mm) flexible extension
3/4 npt(f) swivel inlet with:	
238638	Metric measure 1/2 in (12.7 mm) rigid extension
238639	Metric measure 1/2 in (12.7 mm) flexible extension
1/2 npt(f) swivel inlet with:	
238640	U.S. measure 1/2 in (12.7 mm) rigid extension
238641	U.S. measure 1/2 in (12.7 mm) flexible extension
1/2 npt(f) swivel inlet with:	
238642	Metric measure 1/2 in (12.7 mm) rigid extension
238643	Metric measure 1/2 in (12.7 mm) flexible extension
Bare Valves (No meter or extension)	
With locking trigger and inline flow-through	
238647	1/2 npt(f) swivel inlet; 1/2 npt(f) outlet
238646	3/4 npt(f) swivel inlet; 1/2 npt(f) outlet

### Accu-Shot™ Electronic Meter Specifications

Dimensions	8.72 in L x 4.43 in H x 1.83 in W (221.5 mm L x 112.5 mm H x 46.5 mm W)
Weight	2.2 lbs (1 kg)
Inlet	1/4 npt(f)
Outlet	1/8 npt(f)
Maximum working pressure	5000 psi (345 bar, 34.5 MPa)
Max working temperature	140°F (60°C)
Flow rate	up to 35.3 oz/min (1000 g/min)
Accuracy	±3
Battery	2 x 1.5 v AA Alkaline (standard alkaline batteries)
Manual	309454

### Accu-Shot Electronic Grease Meter Ordering Information

233807	With battery and rigid extension
245694	With 50:1 Fire-Ball, portable pail dispenser, 35 lbs (15.88 kg)
245695	With 50:1 Fire-Ball, cart-mounted pail dispenser, 35 or 70 lbs (15.88 or 31.76 kg)
245696	With 50:1 Fire-Ball, portable package with two wheel cart, 120 lbs (54.43 kg)

### EZ-Shot™ Grease Gun Specifications

Dimensions	21.6 in L x 17.0 in H x 2.8 in W (54.9 mm L x 43.2 mm H x 7.1 mm W)
Weight	2.2 lbs (1 kg)
Maximum working pressure	2900 psi (200 bar, 20 MPa)
Max working temperature	32°F to 122°F (0°C to 50°C)
Dispense quantity	1 cc grease per stroke
Grease capacity	400 g (14 oz) standard cartridge 500 g (16 oz) bulk grease
Battery	7.2 V Ni-Cd
Manual	309446

### EZ-Shot Grease Gun Ordering Information

233808	With 20 in (50.8 cm) flexible extension, rechargeable battery and battery charger
--------	---

### Pro-Shot™ Grease Dispense Valve

242056	1/4 npt(f) inlet with coupler and extension #200389
242055	1/4 npt(f) inlet without coupler or extension
242058	3/8 npt(f) inlet with coupler and extension #200389
242057	3/8 npt(f) inlet without coupler or extension

### Z-Swivel

202577	1/4 npt(m) x 1/4 npt(f)
224569	3/8 npt(m) x 3/8 npt(f)
207948	1/2 npt(m) x 1/2 npt(f)



# Technical Specifications and Ordering Information

## Oil Pumps Quick Reference Matrix

Model Pump Ratio	16 Gal (60 liter) Cover Mt.	55 Gal (200 liter) Bung Mt.	55 Gal (200 liter) Cover Mt.	275 Gal (1040 liter) Bung Mt.	Air Motor Diameter	Max. Fluid Outlet Pressure psi (bar)	Air Operating Range psi (bar)	Cycles per Gallon (cycles/l)	Fluid Flow @ 80 cpm gpm (lpm)	Approx. Air Consumption @ 100 psi (7 bar, 0.7 MPa)	Pumping Distance Guideline* ft (m)	
Fast-Ball® 1:1	222051	N/A	222103	N/A	222104	1.4 in (356 mm)	180 psi (12.4 bar)	40 to 180 psi (2.8 to 12.4 bar)	25 gal (6.6 l)	3.2 gpm (12.1 lpm)	5 cfm	100 ft (30.5 m)
Fast-Flo® UL-Approved 1:1	226944	N/A	226941	N/A	N/A	1.4 in (356 mm)	180 psi (12.4 bar)	40 to 180 psi (2.8 to 12.4 bar)	25 gal (6.6 l)	3.2 gpm (12.1 lpm)	5 cfm	100 ft (30.5 m)
Fast-Flo Stainless Steel; UL-Approved 1:1	226945	N/A	226942	N/A	N/A	1.4 in (356 mm)	180 psi (12.4 bar)	40 to 180 psi (2.8 to 12.4 bar)	25 gal (6.6 l)	3.2 gpm (12.1 lpm)	5 cfm	100 ft (30.5 m)
Fire-Ball 225 3:1	248230	246904	246902	246906	246902	2.25 in (74.4 mm)	540 psi (31 bar)	40 to 180 psi (2.8 to 10.4 bar)	43.5 gal (11.4 l)	1.8 gpm (7.0 lpm)	8.5 cfm	250 ft (76.2 m)
Fire-Ball 300 5:1	225852	225094	225640	225642	225931	3.0 in (76.2 mm)	900 psi (62 bar)	40 to 180 psi (2.8 to 12.4 bar)	28.4 gal (8.6 l)	2.8 gpm (9.3 lpm)	27 cfm	500 ft (152.5 m)
Fire-Ball 425 3:1	237526	N/A	N/A	N/A	N/A	4.25 in (107.9 mm)	540 psi (37 bar)	40 to 180 psi (2.8 to 12.4 bar)	6 gal (1.6 l)	13.4 gpm (50.6 lpm)	32 cfm	250 ft (76.2 m)
6:1	238108	N/A	N/A	N/A	N/A	4.25 in (107.9 mm)	1100 psi (76 bar)	40 to 180 psi (2.8 to 12.4 bar)	12 gal (3.2 l)	6.6 gpm (25.3 lpm)	32 cfm	500 ft (152.5 m)
10:1	205626	N/A	222095	222065	N/A	4.25 in (107.9 mm)	1800 psi (124 bar)	40 to 180 psi (2.8 to 12.4 bar)	19.6 gal (5.2 l)	4.1 gpm (15.4 lpm)	32 cfm	750 ft (228.6 m)

\*Distance may vary depending on line diameter and fluid viscosity

## Grease Pumps Quick Reference Matrix

Model Pump Ratio	35 lb (16 kg)	120 lb (55 kg)	400 lb (180 kg)	Max. Fluid Outlet Pressure psi (bar)	Air Operating Range psi (bar)	Air Motor Diameter	Cycles per lbs (kg)	Approx. Air Consumption @ 100 psi (7 bar, 0.7 MPa)	Pumping Distance Guideline*	Dispense Points	Annual Usage lbs (kg)
Falcon™ 50:1	244044	244045	244046	7500 psi (517 bar)	40-150 psi (2.8-10.4 bar)	2.93 in (74.4 mm)	50 lbs (111.1 kg)	17 cfm	100 ft (30.5 m)	1	5000 lbs (2300 kg)
Fire-Ball 300 50:1	239877	239887	239888	8400 psi (579 bar)	30-140 psi (2.1-9.7 bar)	3 in (76.2 mm)	43.5 lbs (100 kg)	23 cfm	250 ft (76.2 m)	1-2	10,000 lbs (4500 kg)
Fire-Ball 425 50:1	N/A	205394	205395	7500 psi (517 bar)	40-180 psi (2.8-12.4 bar)	4.25 in (107 mm)	15 lbs (33.4 kg)	19 cfm	500 ft (152.4 m)	4+	20,000+ lbs (9100+ kg)
75:1	239731	239729	239730	7500 psi (517 bar)	40-100 psi (2.8-7.0 bar)	4.25 in (107 mm)	23.8 lbs (52.3 kg)	26 cfm	500 ft (152.4 m)	4+	15,000+ lbs (6800+ kg)

\*Distance may vary depending on line diameter and fluid viscosity

## Stationary Grease Pump Packages

	Falcon 50:1*	Fire-Ball 300, 50:1*	Fire-Ball 425, 50:1*	Fire-Ball 425, 75:1*
120 lb	244082	225014	223108	244635
400 lb	244084	225016	225781	244636

\*Units include cover, follower plate, connection hoses (fluid and air) and pump

## Portable Grease Pump Packages

	Falcon 50:1*	Fire-Ball 300, 50:1*
120 lb (Dolly)	244100	225006
400 lb (2-Wheel Cart)	244101	225026

\*Units include pump, dispense hose, Z-swivel, grease valve, cover, follower plate, dolly or cart

## Used Oil Equipment

Description	Part Number	Capacity gallons (l)
Oil King	238866	25 gal (95 l)
Coolant King	248632	25 gal (95 l)
Oil Ace	115599	24 gal (90 l)
Used Oil Receiver w/drum	239301	16 gal (60 l)
Big Hauler	244055	26 gal (98 l)

## Used Oil Evacuation Packages with Air-Operated Diaphragm Pumps (for use with the above used oil equipment)

222090	1 in (25.4 mm)	Double Diaphragm Wall Mount Package
224873	3/4 in (19.05 mm)	Double Diaphragm Wall Mount Package

# Technical Specifications and Ordering Information

## Diaphragm Pumps Quick Reference Matrix

Body/Diaphragm Description	Part Number	Ratio	Max Air psi (bar; MPa)	Free Flow Rate gpm (lpm)	Air Consumption SCFM	Fluid Inlet/Outlet NPT	Fluids
<b>307 3/8 in (9.52 mm)</b> Acetal/Hytrel	D31255	1:1	100 (7; 0.7)	7 (31.8)	7	3/8	OT, WA, WW
<b>515/716 3/4 in (19.05 mm)</b> Aluminum/Buna-N	241906	1:1	100 (7; 0.7)	16 (60.6)	28	3/4	OT, OE, WA, WW
Acetal/Buna Dual Inlet	243669	1:1	100 (7; 0.7)	16 (60.6)	28	3/4	50/50 WW, WA
<b>1040 1 in (25.4 mm)</b> Aluminum/Hytrel	D73525	1:1	120 (8.3; 0.8)	40 (151.4)	40	1	OT, WA, OE, WW
Aluminum/Hytrel (UL)	236265	1:1	120 (8.3; 0.8)	40 (151.4)	40	1	OE, FT, WW
(1) Aluminum/Hytrel (UL)	236267	1:1	50 (3.4; 0.3)	20 (75.7)	20	1	FD
<b>1590 1-1/2 in (38.1 mm)</b> Aluminum/Hytrel	DB3525	1:1	120 (8.3; 0.8)	90 (341.0)	90	1-1/2	OT, OE
<b>2150 2 in (50.8 mm)</b> Aluminum/Hytrel	DF3525	1:1	120 (8.3; 0.8)	150 (567.6)	175	2	OT, OE
<b>3275 3 in (76.2 mm)</b> Aluminum/Hytrel	DK3525	1:1	120 (8.3; 0.8)	275 (1,041.0)	325	3	OT, OE

(1) For use with leaded fuel

## Matrix\*

### Matrix Meter

#### Technical Specification

Maximum working fluid pressure	1500 psi (103 bar, 10.3 MPa)
Operating pressure range	100 to 1500 psi (7 to 103 bar, 0.7 to 10.3 MPa)
Flow range	0.26 to 5 gpm (1 to 18.9 lpm)
Units of measurement	Programmable in pints, quarts, gallons or liters
RF Communication	902-928 MHz frequency hopping, spread - spectrum
Instruction manual	309497

<i>Fluid Key</i>
<i>OT = Oil Transfer</i>
<i>OE = Oil Evacuation</i>
<i>WA = Water, Anti-Freeze</i>
<i>FD = Fuel Dispense</i>
<i>FT = Fuel Transfer</i>
<i>WW = Windshield Wash</i>

### Matrix Meter

#### Ordering Information

246008	Matrix Meter	One battery included. Extension kit is sold separately.
246005	Rigid Extension	
246007	Flexible Extension	
246006	Gear Lube Extension	
248319	Rigid anti-freeze extension	
248320	Flexible anti-freeze extension	
117310	Meter battery	

### Software System

During set up, the Matrix Software program and other files are decompressed and copied to the hard disk. Note: The system administrator function of the program must be set up before using the software or other system components.

This software is not compatible with Apple® Computers, and is not available for the Apple® Operating system.

Minimum computer requirements to run the Matrix software:

- Graco recommends using a dedicated PC with a Pentium III, 500 MHz processor or better. If the system needs to run in a networked configuration, contact your Information Systems (IS) professional before loading the software.
- Microsoft Internet Explorer 5.5 or better
- Microsoft Windows XP – Professional or Home Edition
- At least 128 megabytes (MB) of random-access memory (RAM)
- At least 500 megabytes (MB) to 1 gigabyte (GB) of hard disk space
- One serial port available
- CD-RW or DVD/RW Drive

\*For more information about Matrix, refer to 300599.

### Transceiver

#### Ordering Information

249020	Transceiver and Matrix Full Line Software
117256	Transceiver only

Note: The Matrix Tank Level Monitor and Transceiver Software can be ordered separately using P.N. 249021. For more information about the Tank Level Monitoring part of the Matrix system, see the Tank Level Monitor brochure (Form No. 300619).

### Tank Level Monitor

#### Ordering Information

119274	Tank Level Monitor
--------	--------------------

### Battery Charger and Batteries

#### Ordering Information

117427	Single-Bay Charger	
117429	4-Bay Charger	
117435	Extension Unit	Used to convert a 4-bay charger to either a 5-bay or 6-bay charger. One extension unit is required for a 5-bay conversion and two extension units are used for a 6-bay conversion.
117310	Extra Battery Pack	



# Technical Specifications and Ordering Information

## Hose Reels

### 250 Series

	Low-Pressure	Medium-Pressure	High-Pressure
Inlet	1/2 npsm(m)	1/2 npsm(m)	3/8 npsm(m)
Outlet	1/2 npsm(f)	1/2 npsm(f)	3/8 npsm(f)
Max Pressure (bare reel)	1800 psi (124 bar; 12.4 MPa)	1800 psi (124 bar; 12.4 MPa)	8000 psi (552 bar; 55.2 MPa)
Bearings	brass	brass	brass
Wetted Parts	SST, brass, nitrile rubber	CS, brass, nitrile rubber	CS, brass, leather

### Low-Pressure Hose Reels (for air or water)

240957	Bare Hose Reel
240956*	With 1/2 in x 25 ft (12.7 mm x 7.6 m) hose
240958*	With 1/4 in x 40 ft (6.4 mm x 12.2 m) hose
240959*	With 3/8 in x 40 ft (9.5 mm x 12.2 m) hose

### Medium-Pressure Hose Reels (for motor oil and light lubricants)

240961	Bare Hose Reel
240962*	With 1/2 in x 16 ft (12.7 mm x 4.9 m) hose
240963*	With 1/2 in x 25 ft (12.7 mm x 7.6 m) hose

### High-Pressure Hose Reels (for grease)

240965	Bare Hose Reel
240966*	With 1/4 in x 20 ft (6.4 mm x 6.1 m) hose
240967*	With 1/4 in x 35 ft (6.4 mm x 10.6 m) hose

\*hose inlet kit included

### 350 Series

	Low-Pressure	Medium-Pressure	High-Pressure
Inlet	1/2 npsm(m)	3/8 npsm(m)	3/8 npsm(m)
Outlet	1/2 npsm(f)	3/8 npsm(f)	3/8 npsm(f)
Max pressure (bare reel)	180 psi (12.6 bar; 1.26 MPa)	1800 psi (126 bar; 12.6 MPa)	8000 psi (550 bar; 55 MPa)
Bearings	brass	brass	brass
Wetted parts	carbon steel, nitrile rubber, brass	carbon steel, nitrile rubber, brass	carbon steel, leather, brass

### Low-Pressure Hose Reels with Universal Hose Guide (for air or water)

238211	Hose reel with 3/8 in x 40 ft (9.5 mm x 12.2 m)
238213	Hose reel with 3/8 in x 60 ft (9.5 mm x 18.3 m)
243983	Hose reel with 1/2 in x 50 ft (12.7 mm x 15.3 m)

### Medium-Pressure Hose Reels with Universal Hose Guide (for motor oil and light lubricants)

237020	Bare Hose Reel
237022	With 1/2 in x 50 ft (12.7 mm x 15.3 m)

### High-Pressure Hose Reels (for grease)

237030	Bare Hose Reel
237032	With 1/4 in x 50 ft (6.4 mm x 15.3 m)
237034	With 3/8 in x 50 ft (9.5 mm x 15.3 m)

### 350 and 500 Series Hose Inlet Kits

218549	1/2 in x 2 ft (2.7 mm x 0.6 m), 2000 psi (137.8 bar, 13.7 MPa)
218550	3/8 in x 2 ft (9.5 mm x 0.6 m), 4000 psi (275.6 bar, 27.5 MPa)
224417	1/4 in x 2 ft (6.3 mm x 0.6 m), 5000 psi (344.5 bar, 34.4 MPa)

## 500 Series

	Low- and Medium-Pressure	High-Pressure
Inlet	1/2 npsm(m)	3/8 npsm(m)
Outlet	1/2 npsm(f)	3/8 npsm(f)
Maximum pressure (bare reel)	1800 psi (124 bar; 12.4 MPa)	8000 psi (552 bar; 55.2 MPa)
Bearings	oil-impregnated bronze	oil-impregnated bronze
Wetted Parts	carbon steel, nitrile rubber, polyester elastomer	carbon steel, nitrile rubber, polyester elastomer

### Low-Pressure Hose Reels (for air or water)

224050	Bare Hose Reel
224051	With 3/8 in x 60 ft (9.5 mm x 18.3 m) hose
243982	With 1/2 in x 50 ft (12.7 mm x 15.3 m) hose

### Medium-Pressure Hose Reels (for motor oil and light lubricants)

224050	Bare Hose Reel
224058	With 1/2 in x 50 ft (12.7 mm x 15.3 m) hose

### High-Pressure Hose Reels (for grease)

224060	Bare Hose Reel
224055	With 1/4 in x 50 ft (6.4 mm x 15.3 m) hose
224056	With 3/8 in x 50 ft (9.5 mm x 15.3 m) hose

### Heavy-Duty Dual Hose Reel (for air and fluid) rated to 3000 psi (206 bar, 20.6 MPa)

206941	Dual Hose Reel (Bare Reel)
--------	----------------------------

## 700 Series

	Medium-Pressure
Inlet	1 npt(f)
Outlet	1 npt(f)
Max. pressure (bare reel)	1500 psi (103 bar; 10.3 MPa)
Bearings	self-aligning, sealed ball bearings (steel alloy)
Wetted Parts	carbon steel, Viton®

### Medium-Pressure Oil Dispense Reels rated to 1500 psi (103 bar; 10.3 MPa)

237728	Bare hose reel
237875	With 1/2 in x 75 ft (12.7 mm x 23 m) hose
237881	With 3/4 in x 50 ft (19.1 mm x 15 m) hose
237879	With 3/4 in x 75 ft (19.1 mm x 23 m) hose

### Medium-Pressure Oil Evacuation and Dispense Reels rated to 212 psi (14.6 bar; 1.46 MPa)

241909	Hose reel with 1 in x 30 ft (25.4 mm x 9 m) hose; 24 in (0.3 m) Hg vacuum
241910	Hose reel with 1 in x 50 ft (25.4 mm x 15 m) hose; 24 in (0.3 m) Hg vacuum

### Medium-Pressure Fuel Dispense Reels rated to 125 psi (8.6 bar; 0.86 MPa)

237884	Hose reel with 1 in x 50 ft (25.4 mm x 15 m) hose
206941	Dual Hose Reel (Bare Reel)

## 750 Series

	Medium-Pressure
Inlet	1-1/4 npt(f)
Outlet	1-1/2 npt(f)
Max. pressure (bare reel)	375 psi (26 bar; 2.6 MPa)
Working temperature	150°F (65°C)
Weight	125 lbs (57 kg)
Hose capacity (not included)	50 ft (15.2 m) x 1.25 in ID Hose or 50 ft (15.2 m) x 1.5 in ID Hose

### Medium-Pressure Hose Reels (for high volume applications)

245410	Bare Hose Reel
--------	----------------

## ABOUT GRACO

### PROVEN QUALITY. LEADING TECHNOLOGY.

Founded in 1926, Graco is a world leader in fluid handling systems and components. Graco products move, measure, control, dispense and apply a wide range of fluids and viscous materials used in vehicle lubrication, commercial and industrial settings.

The company's success is based on its unwavering commitment to technical excellence, world-class manufacturing and unparalleled customer service. Working closely with specialized distributors, Graco offers systems, products and technology which set the quality standards in a wide range of fluid handling solutions. Graco provides equipment for lubrication, spray finishing, protective coating, paint circulation, and dispensing sealants and adhesives, along with power application equipment for the contractor industry. Graco's ongoing investment in fluid management and control will continue to provide innovative solutions to a diverse global market.

## GRACO HEADQUARTERS

### AMERICAS

MINNESOTA  
Worldwide Headquarters  
Graco Inc.  
88-11th Avenue N.E.  
Minneapolis, MN 55413

MAILING ADDRESS  
P.O. Box 1441  
Minneapolis, MN 55440-1441  
Tel 612 623-6000  
Fax 612 623-6777

### EUROPE

BELGIUM  
European Headquarters  
Graco N.V.  
Industrieterrein - Oude Bunders  
Slakweidestraat 31  
3630 Maasmechelen, Belgium  
Tel 32 89 770 700  
Fax 32 89 770 777

### ASIA PACIFIC

JAPAN  
Graco K.K.  
1-27-12 Hayabuchi  
Tsuzuki-ku  
Yokohama City, Japan 2240025  
Tel 81 45 593 7300  
Fax 81 45 593 7301

CHINA  
Graco Hong Kong Ltd.  
Representative Office  
Room 118 1st Floor  
No. 2 Xin Yuan Building  
No. 509 Cao Bao Road  
Shanghai, P.R.China 200233  
Tel 86 21 649 50088  
Fax 86 21 649 50077

KOREA  
Graco Korea Inc.  
Choheung Bank Bldg, 4th Floor  
#1599, Gwanyang-Dong, Dongan-Ku  
Anyang-Si, Gyunggi-Do, Korea  
431-060  
Tel 82 31 476 9400  
Fax 82 31 476 9801

Call today for product information or to request a demonstration.

**1.800.533.9655** or visit us at [www.graco.com](http://www.graco.com).

All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice.

Graco Inc. is registered to I.S. EN ISO 9001



上海丛越涂装设备有限公司

Shanghai CONGYUE Spray Technology Engineering Co., Ltd

地址：上海市闵行区瓶北路150弄158号C栋 邮编：201109  
电话：021-64928022，64928002 传真：021-64928778  
专业代理：美国GRACO公司工业及建筑业喷涂设备、涂胶设备、  
润滑油（脂）定量加注设备、流体输送设备  
[www.congyue.com](http://www.congyue.com) E-mail: [congyue@congyue.com](mailto:congyue@congyue.com)

### Sales/Distribution/Service North America

Customer Service  
800-533-9655  
FAX 800-533-9656

GRACO INC.  
P.O. Box 1441  
Minneapolis, MN 55440-1441

